











TECHNICAL SPECS

Model		V3	V 5	V8	V10	V12	V15	V20	V30	V35
Excavator size	ton	2 - 4	3 - 6	5 - 10	7 - 12	10 - 15	13 - 18	15 - 25	25 - 35	30 - 40
Hydraulic flow	gpm	5 - 15	5 - 15	10 - 20	10 - 20	10 - 20	10 - 20	10 - 20	20 - 31	20 - 31
Oil pressure (max)	psi	4600 PSI maximum								
Load Volume	yd ³	0.1	0.27	0.5	0.55	0.81	0.95	1.57	1.57	1.83
Material Output Size	in	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0
Bar Diameter	in	0.8	1	1.2	1.2	1.2	1.2	1.2	1.75	1.75
Bucket Width	in	28	31.5	39	47	47	52	59	59	63
Weight (w/o bracket)	lbs	375	595	1080	1430	1895	2200	3175	3880	4080

^{*} When at minimum carrier weight, the working range may be limited due to attachment weight











+1 814-466-7134 info@RockzoneAmericas.com RockzoneAmericas.com 801 Pleasant View Blvd Bellefonte, PA 16823 USA



RockZone Americas is part of Exodus Global, a family-owned company based in Superior, Wisconsin











April 2025: Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings contained in this document are for illustration only. Please refer to the relevant Operating Manual for instructions on the proper use of this equipment. Failure to adhere to the appropriate Operating Manual when using our products or otherwise negligent behavior can result in serious injury or death. The standard written warranty is the only warranty that applies to our products. Rokla GmbH provides no further warranty, either expressly nor implied.